

Diesin Pro**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Diesin Pro

Product code : 117191E

Use of the Substance/Mixture : Cleaner and disinfectant

Substance type: : Mixture

For professional users only.

Product dilution information : 0.1 % - 0.5 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Sanitary cleaner. Manual process
Surface disinfectant. Manual process
Floor cleaner. Manual process
Surface disinfectant. Spray and rinse manual process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 07.06.2023
Version : 1.4

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD

Diesin Pro

Acute toxicity, Category 4	H302
Skin corrosion, Sub-category 1A	H314
Serious eye damage, Category 1	H318
Acute aquatic toxicity, Category 1	H400
Chronic aquatic toxicity, Category 2	H411

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H302
H314
H400
H411Harmful if swallowed.
Causes severe skin burns and eye damage.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.Supplemental Hazard
Statements

: EUH071

Corrosive to the respiratory tract.

Precautionary Statements

: **Prevention:**P260
P273
P280Do not breathe spray.
Avoid release to the environment.
Wear protective gloves/ eye protection/ face
protection.**Response:**P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately
all contaminated clothing. Rinse skin with water
or shower.P305 + P351 + P338 IF IN EYES: Rinse cautiously with water
for several minutes. Remove contact lenses, if
present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:
N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine
benzalkonium chloride**Product AT USE DILUTION**No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s)
required**2.3 Other hazards****Product AS SOLD**

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures**

Diesin Pro**Product AS SOLD**
Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
2-phenoxyethanol	122-99-6 204-589-7 01-2119488943-21	Acute toxicity Category 4; H302 Serious eye damage/eye irritation Category 1; H318 Specific target organ toxicity - single exposure Category 3; H335	>= 10 - < 20
N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine	2372-82-9 219-145-8 01-2119980592-29	Acute toxicity Category 3; H301 Skin corrosion Category 1A; H314 Serious eye damage Category 1; H318 Specific target organ toxicity - repeated exposure Category 2; H373 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 M = 10 M(Chronic) = 1	>= 5 - < 10
benzalkonium chloride	68424-85-1 270-325-2 01-2119965180-41	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 M = 10 M(Chronic) = 1	>= 5 - < 10
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335 Specific target organ toxicity - single exposure Category 3 H335 5 - 100 %	>= 1 - < 2.5
C10-16 Polyglycoside	110615-47-9 01-2119489418-23	Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Serious eye damage/eye irritation Category 1 > 12 - 100 % Serious eye damage/eye irritation Category 2 1 - 12 % Skin corrosion/irritation Category 2 30 - 100 %	>= 1 - < 2.5
d-glucopyranose, oligomeric, decyl octyl glycosides	68515-73-1 500-220-1 01-2119488530-36	Serious eye damage Category 1; H318 Serious eye damage/eye irritation Category 1 > 10 - 100 % Non-hazardous substance 1 - 10 %	>= 1 - < 2.5

Diesin Pro

Reaction mass of [[(2-hydroxyethyl)imino]bis(methylene)]bisphosphonic acid and Phosphonic acid, P-[(tetrahydro-2-hydroxy-2-oxido-4H-	911-811-2 01-2119972017-37	Corrosive to metals Category 1; H290 Acute toxicity Category 3; H301 Skin corrosion Category 1A; H314 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 0.1 - < 0.25
Substances with a workplace exposure limit :			
sodium hydroxide	1310-73-2 215-185-5 01-2119457892-27	Skin corrosion Category 1A; H314 Corrosive to metals Category 1; H290 Skin corrosion Category 1A H314 >= 5 % Skin corrosion Category 1B H314 2 - < 5 % Skin irritation Category 2 H315 0.5 - < 2 % Eye irritation Category 2 H319 0.5 - < 2 %	>= 0.1 - < 0.25

Product AT USE DILUTION
Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine	2372-82-9 219-145-8 01-2119980592-29	Acute toxicity Category 3; H301 Skin corrosion Category 1A; H314 Serious eye damage Category 1; H318 Specific target organ toxicity - repeated exposure Category 2; H373 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 M = 10 M(Chronic) = 1	>= 0.025 - < 0.1
benzalkonium chloride	68424-85-1 270-325-2 01-2119965180-41	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 M = 10 M(Chronic) = 1	>= 0.025 - < 0.1

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures****Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Diesin Pro

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Diesin Pro

Product AS SOLD

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Diesin Pro

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

- Advice on safe handling : Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities**Product AS SOLD**

- Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : 0 °C to 25 °C

Product AT USE DILUTION

- Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses**Product AS SOLD**

- Specific use(s) : Sanitary cleaner. Manual process
Surface disinfectant. Manual process
Floor cleaner. Manual process
Surface disinfectant. Spray and rinse manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Product AS SOLD****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
monoethanolamine	141-43-5	TWA	1 ppm 2.5 mg/m ³	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	3 ppm 7.6 mg/m ³	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for		

Diesin Pro

		which there are concerns that dermal absorption will lead to systemic toxicity.		
sodium hydroxide	1310-73-2	STEL	2 mg/m3	UKCOSSTD

DNEL

sodium hydroxide	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3
------------------	---	---

8.2 Exposure controls**Product AS SOLD****Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A-P

Product AT USE DILUTION**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker

Diesin Pro

exposure to airborne contaminants.

Individual protection measures

Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.
Eye/face protection (EN 166)	: No special protective equipment required.
Hand protection (EN 374)	: No special protective equipment required.
Skin and body protection (EN 14605)	: No special protective equipment required.
Respiratory protection (EN 143, 14387)	: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Colour	: clear, light yellow	colourless
Odour	: amine-like	odourless
pH	: 10.5 - 11.4, 100 %	9.1 - 9.8
Flash point	: closed cupNot applicable.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Relative density	: 1.005 - 1.011	
Water solubility	: soluble	

Diesin Pro

Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NO_x)

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : 1,564 mg/kg

Diesin Pro

Acute inhalation toxicity	: 4 h Acute toxicity estimate : > 5 mg/l Test atmosphere: dust/mist
Acute dermal toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.
Aspiration toxicity	: There is no data available for this product.

Components

Acute oral toxicity	: 2-phenoxyethanol LD50 rat: 1,394 mg/kg N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine LD50 rat: 261 mg/kg benzalkonium chloride LD50 rat: 344 mg/kg monoethanolamine LD50 rat: 1,089 mg/kg C10-16 Polyglycoside LD50 rat: > 5,000 mg/kg d-glucopyranose, oligomeric, decyl octyl glycosides LD50 rat: > 5,000 mg/kg
---------------------	--

Components

Acute inhalation toxicity	: monoethanolamine 4 h LC50 rat: > 1.6 mg/l Test atmosphere: dust/mist
---------------------------	---

Components

Acute dermal toxicity	: 2-phenoxyethanol LD50 rabbit: 2,250 mg/kg benzalkonium chloride LD50 rabbit: 3,340 mg/kg monoethanolamine LD50 rabbit: 1,025 mg/kg d-glucopyranose, oligomeric, decyl octyl glycosides LD50 rabbit: > 2,000 mg/kg
-----------------------	--

Potential Health Effects

Diesin Pro

Product AS SOLD

- Eyes : Causes serious eye damage.
- Skin : Causes severe skin burns.
- Ingestion : Harmful if swallowed. Causes digestive tract burns.
- Inhalation : May cause nose, throat, and lung irritation.
- Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

- Eye contact : Redness, Pain, Corrosion
- Skin contact : Redness, Pain, Corrosion
- Ingestion : Corrosion, Abdominal pain
- Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

- Eye contact : No symptoms known or expected.
- Skin contact : No symptoms known or expected.
- Ingestion : No symptoms known or expected.
- Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Product AS SOLD

- Environmental Effects : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Product AS SOLD
Product**

- Toxicity to fish : no data available
- Toxicity to daphnia and other aquatic invertebrates : no data available
- Toxicity to algae : no data available

Components

- Toxicity to fish : 2-phenoxyethanol 96 h LC50 Pimephales promelas (fathead minnow): 344 mg/l
- C10-16 Polyglycoside 96 h LC50 Brachydanio rerio (zebrafish): 2.95 mg/l

Components

- Toxicity to daphnia and other : 2-phenoxyethanol 48 h EC50 Daphnia magna (Water flea): > 500

Diesin Pro

aquatic invertebrates

mg/l

benzalkonium chloride 48 h EC50 Daphnia magna (Water flea):
0.016 mg/lmonoethanolamine 48 h LC50 Daphnia magna (Water flea): 65
mg/lC10-16 Polyglycoside 48 h EC50 Daphnia magna (Water flea): 7
mg/lReaction mass of [[(2-
hydroxyethyl)imino]bis(methylene)]bisphosphonic acid and
Phosphonic acid, P-[(tetrahydro-2-hydroxy-2-oxido-4H-48 h EC50:
128 mg/l

sodium hydroxide 48 h EC50 Daphnia magna (Water flea): 40 mg/l

Components

Toxicity to algae

: 2-phenoxyethanol 72 h EC50 Desmodesmus subspicatus (green
algae): > 100 mg/lN-(3-aminopropyl)-N-dodecylpropane-1,3-diamine 72 h EC50:
0.014 mg/lC10-16 Polyglycoside 72 h EC50 Desmodesmus subspicatus
(green algae): 12.5 mg/ld-glucopyranose, oligomeric, decyl octyl glycosides 72 h EC50: 18
mg/l**12.2 Persistence and degradability****Product**

Biodegradability

: The surfactants contained in the product are biodegradable
according to the requirements of the detergent regulation
648/2004/EC**Components**

Biodegradability

: 2-phenoxyethanol Result: Readily biodegradable.

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine Result: Readily
biodegradable.

benzalkonium chloride Result: Biodegradable

monoethanolamine Result: Readily biodegradable.

C10-16 Polyglycoside Result: Readily biodegradable.

d-glucopyranose, oligomeric, decyl octyl glycosides Result:
Readily biodegradable.Reaction mass of [[(2-
hydroxyethyl)imino]bis(methylene)]bisphosphonic acid and
Phosphonic acid, P-[(tetrahydro-2-hydroxy-2-oxido-4H-Result:
Biodegradable

Diesin Pro

sodium hydroxide Result: Not applicable - inorganic

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Product AT USE DILUTION

Product : Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.

Diesin Pro

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION**Product AS SOLD**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 1903
14.2 UN proper shipping name : DISINFECTANT, LIQUID, CORROSIVE, N.O.S.
(quaternary ammonium compound, Alkylamine(s))
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : Yes
14.6 Special precautions for user : None

Air transport (IATA)

14.1 UN number : 1903
14.2 UN proper shipping name : Disinfectant, liquid, corrosive, n.o.s.
(quaternary ammonium compound, Alkylamine(s))
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : Yes
14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 1903
14.2 UN proper shipping name : DISINFECTANT, LIQUID, CORROSIVE, N.O.S.
(quaternary ammonium compound, Alkylamine(s))
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : Yes
14.6 Special precautions for user : None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION

Diesin Pro

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents : 5 % or over but less than 15 %: Cationic surfactants
Regulation EC 648/2004 less than 5 %: Non-ionic surfactants
Contains: Disinfectants

Seveso III: Directive : ENVIRONMENTAL HAZARDS E1
2012/18/EU of the European Lower tier : 100 t
Parliament and of the Council Upper tier : 200 t
on the control of major-
accident hazards involving
dangerous substances.

Candidate List of Substances : Not applicable.
of Very High Concern for
Authorisation

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)
Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Acute toxicity 4, H302	Calculation method
Skin corrosion 1A, H314	Calculation method
Serious eye damage 1, H318	Calculation method
Acute aquatic toxicity 1, H400	Calculation method
Chronic aquatic toxicity 2, H411	Calculation method

Full text of H-Statements

H290 May be corrosive to metals.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous

Diesin Pro

Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios**Exposure Scenario: Surface disinfectant. Spray and rinse manual process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Diesin Pro**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC11** Non industrial spraying

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Diesin Pro

Skin Protection : see section 8

Respiratory Protection : see section 8

Exposure Scenario: Sanitary cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Diesin Pro

Exposure Scenario: Surface disinfectant. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Exposure Scenario: Floor cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Diesin Pro

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8